



Card-Type PLC



1+15
Single PLC MPU can expand 15 modules, up to 256 points



Cloud Engine
Remote program & monitor PLC through Haiwell Cloud



Motion Control
Supports 4 points 200 kHz high-speed pulse input and output



Mix-type MPU
PLC MPU integrated with digital and analog IO



Ethernet +
Support Ethernet + RS485 work simultaneously



Easy Wiring
Direct pressure terminal block, easy connecting

AC Series Card-type PLC MPU

Model	Specification							Dimension WxHxD(mm)
24VDC	DI	DO	AI	AO	COM Port	Power	Max. Exp.	
AC10S0R	6	4 Relay			TCP+485	<4.8W	3	 40×95×65
AC10S0T	6	4 Transistor NPN			TCP+485	<4.8W	3	
AC10S0P	6	4 Transistor PNP			TCP+485	<4.8W	3	
AC16S0R	8	8 Relay			TCP+485	<4.8W	3	
AC16S0T	8	8 Transistor NPN			TCP+485	<4.8W	3	
AC16S0P	8	8 Transistor PNP			TCP+485	<4.8W	3	
AC12M0R	4	4 Relay	2	2	TCP+485	<3.6W	3	
AC12M0T	4	4 Transistor NPN	2	2	TCP+485	<3.6W	3	
AC12M0P	4	4 Transistor PNP	2	2	TCP+485	<3.6W	3	


*AC Series does not support A01RS Module

AT Series Card-type PLC MPU

Model	Specification									Dimension WxHxD(mm)
24VDC	DI	DO	AI	AO	Pulse Input	Pulse Output	COM Port	Power	Max. Exp.	
AT16S0R	8	8 Relay			2 Channels A/B phase 4points 200K		TCP+485	<4.8W	15	 40×95×65
AT16S0T	8	8 Transistor NPN			2 Channels A/B phase 4points 200K	2 Channels A/B phase 4points 200K	TCP+485	<4.8W	15	
AT16S0P	8	8 Transistor PNP			2 Channels A/B phase 4points 200K	2 Channels A/B phase 4points 200K	TCP+485	<4.8W	15	
AT12M0R	4	4 Relay	2	2	1 Channel A/B phase 2points 200K		TCP+485	<3.6W	15	
AT12M0T	4	4 Transistor NPN	2	2	1 Channel A/B phase 2points 200K	1 Channel A/B phase 2points 200K	TCP+485	<3.6W	15	
AT12M0P	4	4 Transistor PNP	2	2	1 Channel A/B phase 2points 200K	1 Channel A/B phase 2points 200K	TCP+485	<3.6W	15	

AH Series Card-type PLC MPU

Model	Specification							Dimension WxHxD(mm)
24VDC	DI	DO	Pulse Input	Pulse Output	COM Port	Power	Max. Exp.	
AH16S0R	8	8 Relay	4 Channels A/B phase 8points 200K		TCP+485	<4.8W	15	 40×95×65
AH16S0T	8	8 Transistor NPN	4 Channels A/B phase 8points 200K	4 Channels A/B phase 8points 200K	TCP+485	<4.8W	15	
AH16S0P	8	8 Transistor PNP	4 Channels A/B phase 8points 200K	4 Channels A/B phase 8points 200K	TCP+485	<4.8W	15	



Digital I/O Modules

Model	Specification				Dimension WxHxD(mm)
24VDC	DI	DO	COM Port	Power	
A08DI	8		/	<2.4W	 25×95×65
A08DOR		8 Relay	/	<4.8W	
A08DOT		8 Transistor NPN	/	<4.8W	
A08DOP		8 Transistor PNP	/	<4.8W	
A08XDR	4	4 Relay	/	<2.4W	
A08XDT	4	4 Transistor NPN	/	<2.4W	
A08XDP	4	4 Transistor PNP	/	<2.4W	
A16DI	16		/	<2.4W	 25×95×65
A16DOR		16 Relay	/	<8.4W	
A16DOT		16 Transistor NPN	/	<8.4W	
A16DOP		16 Transistor PNP	/	<8.4W	
A16XDR	8	8 Relay	/	<4.8W	
A16XDT	8	8 Transistor NPN	/	<4.8W	
A16XDP	8	8 Transistor PNP	/	<4.8W	

Analog I/O Modules

Model	Specification					Dimension WxHxD(mm)
24VDC	AI	AO	Conversion Accuracy	COM Port	Power	
A04AI	4		12bit	/	<2.4W	 25×95×65
A04AO		4	12bit	/	<2.4W	
A04XA	2	2	12bit	/	<2.4W	
A08AI	8		12bit	/	<2.4W	
A08AO		8	12bit	/	<3.6W	
A08XA	4	4	12bit	/	<3.6W	

Temperature I/O Modules

Model	Specification				Dimension WxHxD(mm)
24VDC	Sensor	Conversion Accuracy	COM Port	Power	
A04TC	4 Thermocouple	16bit	/	<2.4W	 25×95×65
A04RC	4 Thermal Resistance	16bit	/	<2.4W	
A08TC	8 Thermocouple	16bit	/	<2.4W	
A04DT	4 Channels digital temperature & humidity sensor	9~12bit	/	<2.4W	

Communication I/O Modules

Model	Specification	Power	Dimension(mm) WxHxD
A01RS	With isolation, 1 RS232/RS485 communication port. Supports Modbus RTU/ASCII, Freedon comomunication protocol, Haiwellbus, 1200~115200bps Supports 8,N,1	<2.4W	 25×95×65



海纳百川
诚信有为

Xiamen Haiwell Technology Co., Ltd.

Headquarters: 13-14/F, C03 Building, Phase III Software Park, Jimei District, Xiamen, Fujian, China
Factory: 4F, No. 336-2, Anbian Nan Road, Torch High-tech Zone (Xiang'an) Industrial Zone, Xiang'an District, Xiamen, Fujian, China. 361101
Tel: +86-592-2230312 Hotline: +86-4000-360-362
Email: service@haiwell.com
Website: www.haiwell.com



Haiwell Cloud APP



Haiwell WeChat



The parameters of product are subject to changes without prior notice. (Ver. I - 202310)