

No front and rear enclosures
for easy installation and easy modular integration



N Series SmartLink HMI

10 Highlights

Enable simple connection between HMI, mobile phone, tablet, computer,TV,camera and other HMIs in local area network.

Enable simple connection between HMI, mobile phone, tablet, computer,TV, camera and other HMIs over the Internet.

Allow remote access for multiple concurrent users without SCADA in the cloud or VNC connection.

Provide data transmission and data storage in any public or private server.

Integrate data with ERP, MES or other applications by MQTT, OPC UA, HTTP,TCP and etc.

Embed the display of HMI in other applications like software, APP and etc.

Include intelligent functions such as TTS output, intercom, audio playing and etc.

Use mobile phone as a scanner to scan barcode and enter information in HMI.

Apply to data visualization or centralized control on large screen by TVBOX.

Use innovative design including HD screen, design without shell and eSIM.

Model List

Model	TFT Screen	Storage	LAN+COM	USB	Voice	WiFi	Wireless	Hole Size	Dimension W*H*D
N4	4.3" 800*480 HD	4G+512M	1+2	1	Yes			108x70mm	125x78x32mm
N4-G		4G+512M	1+2	1	Yes		China 4G		
N4-W		4G+512M	1+2	1	Yes	Yes			
N4-E		4G+512M	1+2	1	Yes		Global 4G		
N7	7" 1024*600 HD	4G+512M	1+2	1	Yes			168x103mm	184x118x24mm
N7-G		4G+512M	1+2	1	Yes		*Built in eSIM		
N7-W		4G+512M	1+2	1	Yes	Yes			
N7-GW		4G+512M	1+2	1	Yes	Yes	*Built in eSIM		
N10	10.1" 1024*600 HD	4G+512M	1+2	1	Yes			238x146mm	248x160x23mm
N10-G		4G+512M	1+2	1	Yes		*Built in eSIM		
N10-W		4G+512M	1+2	1	Yes	Yes			
N10-GW		4G+512M	1+2	1	Yes	Yes	*Built in eSIM		

Products Features



Connection in LAN

All models have built-in IIoT technology which enables local access and open interface without internet.




Remote access

With the real-time control solution developed by Haiwell, concurrent users can remotely access gateway by APP and desktop.



Cloud maintenance

It's easier for manufacturers to manage equipments by using remote maintenance function.



Secure access

The remote access needs to be identified by the A/B key security mechanism. The remote control can be configured to be authorized on gateway.




Data security

The user data is not stored in Haiwell cloud. All the data can be stored in private or public server assigned by users.



Web API

Users can get the data and control device on their own platform or software by Web API in local area network or over Internet.




IoT platform

All models support the connection to Alibaba Cloud IoT, AWS IoT and Google Cloud IoT Core.



MQTT protocol


MQTT protocol is supported and applied to the connection with ERP/MES/database.






Digital display board

The production data, device state and video surveillance can be viewed on large screen by connecting with TVBOX. It can be applied to data visualization and centralized control.



Remote centralized control

All the data of remote devices can be acquired through MQTT broker for centralized control. Users don't even need to deploy server if using cloud data center.



Text to speech

The English text can be converted into voice through built-in speaker. Audio files can also be played.



Support text to speech

Support voice intercom



usb to audio adapter


Support voice broadcast

Support remote intercom and broadcast with mobile phone




Display integration

The display of gateway can be embedded in other applications such as software, website, APP and etc so that they have remote access to gateway.



Mobile scanner

You can turn your mobile phone into a barcode scanner and enter information everywhere. It's more convenient than external scanner.



规格参数

规格参数		N4"	N7"	N10"
Software	Programming software	Haiwell Cloud SCADA		
Display	Screen size	4.3" TFT	7" TFT	10.1" TFT
	Resolution	800x480 pixels		1024x600 pixels
	Color	16.7M		
	Brightness	450 cd/m2		
	Viewing angle	80°/80°/80°/80°		85°/85°/85°/85°
Backlight	Touch panel type	Analog resistive film		
	Type	LED		
	Life	50,000 hours		
Hardware	Auto sleep function	Yes		
	Flash	4GB		
	RAM	512M		
	Ethernet port	10/100 Base-T*1		
	Serial port	COM1:RS232*1 COM2:RS485*1		
	USB HOST	USB2.0 *1		
Power	RTC	Yes		
	Rated input power	24V DC±20%		
	Power consumption	6W@24V DC	7.5W@24V DC	9W@24V DC
	Power protection	Surge protection and anti-reverse protection		
	Withstand voltage	500VAC		
Environment	Insulation resistance	50MΩ @500VDC or more		
	Vibration resistance	10 - 25Hz: 2G/30 minutes in each of X,Y or Z direction		
	Cooling method	Natural air circulation		
	Storage temperature	-20 ~70°C		
Structure	Operating temperature	-10°C ~ 60°C		
	Relative humidity	10 ~ 90% RH (non-condensing)		
	Operating environment	Prevention of dust, moisture, corrosion, electric shock and external shock		
	External dimensions (WxHxD)	125x78x32mm	184x118x24mm	248x160x23mm
	Panel cut dimensions (WxH)	108x70mm	168x103mm	238x146mm
Function	Weight	0.3kg	0.45kg	0.75kg
	Installation	Vacancy fixation		
	WiFi	Optional (802.11b/g/n)		
	Wireless	Optional (4G eSIM)		



海纳百川
诚信有为

XIAMEN HAIWELL TECHNOLOGY CO., LTD.

Headquarters: 13-14/F, C03 Building, Phase III Software Park,
Jimei District, Xiamen, Fujian, China
Factory: 4F, No. 336-2, Anbian Nan Road, Torch High-tech Zone
(Xiang 'an) Industrial Zone, Xiang 'an District, Xiamen, Fujian,
China. 361101
Tel: +86-592-2230312 Hotline: +86-4000-360-362
Email: service@haiwell.com
Website: www.haiwell.com



Haiwell APP



Haiwell Wechat

The parameters of product are subject to changes without prior notice. (Ver 1 - 202402)